


The **LOADER RANGE**

EZA POWER CHARGERS



220V

Charging via 220V DC mains, from 10Amp to 70Amp



LITHIUM

Battery health preserved by respecting the charging curve



RECHARGE

Enjoy the security of an energy-saving mode with automatic standby



LED INDICATOR

LED N°1 (red): load on LED N°2 (red): load on LED N°2 (green): battery charged

EZA HAS A COMPLETE RANGE OF AC / DC CHARGERS. RANGING FROM 3.5 TO 70 AMPS, THEY PROVIDE HIGH-PERFORMANCE CHARGING OF YOUR LEISURE VEHICLE'S AUXILIARY BATTERY VIA THE 230V MAINS SUPPLY.

From the 10A model upwards, these chargers incorporate multiple charge algorithm settings adapted to the different types of batteries on the market (Lithium, AGM, Gel, Acid, etc.), as well as iUoU technology (voltage/current mix) on all 3 phases (Bulk / Absorption / Floating), all to help your batteries last longer. The dedicated models or those incorporating the Lithium profile provide sufficient end-of-charge voltage for perfect cell balancing. The 3.5A model completes the range, providing maintenance charging for Acid, AGM and Gel batteries during winter storage periods.



The **LOADER RANGE**

EZA POWER CHARGERS

PRODUCT FEATURES	3,5A	10A	20A	30A	70A
	466149	466170	466156	466158	470171
NOMINAL power	3,5A	10A	20A	30A	70A
INPUT RANGE AC CURRENT	200 - 260V		180 - 260V		200 - 264V
DC OUTPUT VOLTAGE	12V				
TECHNOLOGY	IUoU LOAD PROFILE	LITHIUM CHARGING PROFILE	IUoU LOAD PROFILE		IUoU LOAD PROFILE
BATTERY TYPE	AGM/GEL/ACIDE	AGM/GEL/ACIDE/ LITHIUM	AGM/GEL/ACIDE/ LITHIUM	AGM/GEL/ACIDE/ LITHIUM	LITHIUM
BATTERY TYPE SELECTION	AUTOMATIC	MANUAL	MANUAL	MANUAL	AUTOMATIC
APPLICATION	MAINTENANCE/ WINTERING	BATTERY MOVER	BATTERY MOVER	AUXILIARY BATTERIES	AUXILIARY BATTERIES
REVERSE POLARITY PROTECTION	YES				
SHORT-CIRCUIT PROTECTION	YES				
OVERHEATING PROTECTION	YES				
MODE OF COMMUNICATION	LEDS				
AUTHORISED POSITION/FIXING	Horizontal and vertical				
AC CONNECTICAL	1.35 m cable	230V / 1m cable	230V / 1m cable	230V / 1m cable	CABLES SUPPLIED
DC CONNECTICAL	1 m cable	DC M6 terminals	DC M6 terminals	DC M6 terminals	
DIMENSIONS IN MM PRODUCT (L x W x H)	118*71*80	160*150*70	185*150*70	235*150*70	308*220*75
NET WEIGHT	0,6KG	1,1KG	1,6KG	1,8KG	3,3KG
DELIVERED WITH	Leaflet + fuse				
CERTIFICATIONS, APPROVALS	CE (EMC, LVD), RoHs, IP60, R11 environment compatible	CE (EMC, LVD), RoHs, R10 environmental compatibility			
WARRANTY	2 YEARS				

LOGISTICS DATA	3,5A	10A	20A	30A	70A
	466149	466170	466156	466158	466148
EAN CODE	3700628272496	3700628270249	3700628255062	3700628255086	3663970000486
CUSTOMS CODE	8504405590				
SUPPLIER ORIGIN	CHINA				
PACKAGING	COLOR GIFT BOX				
GROSS WEIGHT (KG)	1,1KG	1,7KG	2,3KG	2,5KG	4KG
QTY CARTON	1				

To access to the
digital version,
scan this QR Code.



EZA FT CHARGEUR EZA POWER LIX



Need some advice ?
Contact the Hotline on **+44 1376 428 006**



All our products come with a
2 Year Warranty



More information on
www.eza.fr