

The DC-DC BOOSTER RANGE

DC-DC EZA MBB1240



IP67 STANDARD

Meets IP67 standards for water resistance and dust



TECHNOLOGY

Synchronous switching technology that enables a 12V battery to be charged from vehicles fitted with 12V or 24V alternators



SILENT

This charger gives your battery a silent boost



LOAD QUALITY

Features an algorithm that adapts charging power depending on the state of the battery.

Latest-generation DC/DC charger that combines the alternator's charge with the solar charge and charges your auxiliary battery faster. Compatible with the latest vehicles fitted with intelligent alternators and with all auxiliary battery technologies. Safe operation thanks to protection against overvoltage, overheating, reverse polarity and low voltage.

Designed to operate in the harshest environments, its high IP rating is a guarantee of robustness. It is also compact and easy to install.

DOUBLE ENTRANCE

Allows the battery to be charged from two energy sources simultaneously: solar and motor, with automatic charge distribution.



PRODUCT FEATURES	DC-DC EZA MBB1240
	496279
RATED LOAD CURRENT	40 A
INPUT VOLTAGE	Alternator: 9-32V Solar: 10-32V
ALTERNATOR COMPATIBILITY	EURO 6 / EURO 6+
LOAD TYPE	MIXED: MOTOR/SOLAR
BATTERY TYPE	ACID/AGM/GEL/LITHIUM
SOLAR REGULATION	MPPT / 500W
VACUUM SELF-CHARGING	9mA
CUT-OFF THRESHOLD	11.8-12.8V
FLOATING TRIP THRESHOLD	13.6
OVERHEATING PROTECTION	YES
HOUSING TYPE	ABS
DIMENSIONS IN MM PRODUCT (L x W x H)	184 x 129 x 43
NET WEIGHT	950g
SUPPLIED WITH	NOTICE
CERTIFICATIONS, APPROVALS	CE/MSDS/UN38.3 / E13 R10 environment compatible
WARRANTY	2 ANS

LOGISTICS DATA	DC-DC EZA MBB1240
	496279
CODE EAN	3700628272809
CODE DOUANIER	850710203080
ORIGINE FOURNISSEUR	CHINA
DIMENSIONS IN MM PACKAGED PRODUCT (L x W x H)	290 x 190 x 118

To access the digital version, scan this QR Code.



EZA FT DC-DC MBBP1240 UK



Need some advice ?

Contact the Hotline on **+44 1376 428 006**



All our products come with a **2 Year Warranty**



More information on **www.eza.fr**