

AIR CONDITIONING RANGE

INVERTER TECHNOLOGY



Remote control with Turbo mode



THE STRENGTHS OF INVERTER TECHNOLOGY



CONTROLLED POWER

Intelligent management provides active, permanent temperature control to ensure the best possible energy consumption reduced by 50%.



HIGH PERFORMANCE

Heating and cooling power delivered with low energy consumption. High SEER and SCOP indices.

SMART POWER roof-top air conditioners feature INVERTER compression technology, which is more discreet and economical than conventional compressors. They come in 2 models, 2700W and 3600W, for maximum power output with very low energy consumption.

Their designs combine this new compressor technology with meticulous assembly using Silentbloc, making the **SMART POWER** one of the quietest on the market (between 40 and 50dB). Equipped with a reversible heat pump, it can provide cooling or heating air with an adjustable temperature range from 16 to 30°C. The warm mode allows operation even in sub-zero temperatures, and can start at -5°C.



EXTRA-SLIM DIFFUSER

The EZA roof-mounted air-conditioning unit features ambient lighting and an LCD display. With its extra-slim dimensions, it can be installed on the central rooflight or in the bedroom.



R32 refrigerant gas

EZA roof-top air conditioners use R32 refrigerant gas, which is more environmentally friendly in terms of CO² emissions. It is 2 times more environmentally friendly than R134A and 4 times more than R410A. It is currently the safest and most environmentally-friendly standard authorised for refrigeration production.

PRODUCT FEATURES	703431	703432
REFRIGERANT FLUID		R32
REVERSIBLE COOLING / HEATING (HEAT PUMP)		YES
COOLING POWER in W	2650	3600
COOLING POWER in Btu/h	9042	12283
SEER	2,79	3,27
Consumption COLD in Watts /Ampere	TURBO MODE (max.) : 1025W / 4,4A NORMAL MODE : 950W / 4,2A REGULATION MODE (Min.) : 550W / 2,5A	TURBO MODE (max.) : 1350W / 5,8A NORMAL MODE : 1100W / 4,7A REGULATION MODE (Min.) : 600W / 2,6A
HOT POWER in W		2500
HOT POWER in Btu/h		8530
SCOP		3,21
Consumption HOT in Watts/Ampere	TURBO MODE (max.) : 970W / 4,2A NORMAL MODE : 780W / 3,4A REGULATION MODE (Min.) : 430W / 1,9A	TURBO MODE (max.) : 1000W / 4,3A NORMAL MODE : 950W / 3,5A REGULATION MODE (Min.) : 450W / 2,1A
PEAK CURRENT ON START-UP	NONE / Soft start (< 1A)	NONE / Soft start (< 1A)
OPERATING TEMPERATURE RANGE	WARM -5° à +24° - COLD +18° à +46°	
NOISE LEVEL (dBA)	43-54	
MINI/MAXI AIR FLOW (m3/h)	225 - 340	
DIFFUSER	Extra-slim 2 outputs	
LIGHTING	Atmosphere - Led	
COLOURS	WHITE	
MOUNTING ON APERTURE	40 X 40 cm	
TEMPERATURE RANGES	16 to 30° adjustable	
MAXIMUM OPERATING SLOPE (in %)	0,08	
RECOMMENDED FOR VEHICLES	< ou = 8m	> 8m
DIMENSIONS IN MM BARE OUTSIDE UNIT (L x W x H)	1077*720*283	
DIMENSIONS IN MM DIFFUSER (L x W x H)	610*485*49	
NET WEIGHT	Unit 29,5 Kg / Diffuser 2,7 Kg	
SUPPLIED WITH	MULTIFUNCTION REMOTE CONTROL, COOLING UNIT AND DIFFUSER, STAINLESS STEEL SCREWS AND BOLTS	
PROTECTION FACTOR	IPX4	
CERTIFICATIONS, APPROVALS	CE environment friendly R10	
WARRANTY	2 YEARS	

LOGISTICS DATA	703431	703432
EAN CODE	3700628271086	3700628272892
CUSTOMS CODE		84151010
SUPPLIER ORIGIN		CHINA
DIMENSIONS IN MM PACKAGED PRODUCT (L x W x H)		1116*783*405
PACKAGING		BROWN CARTON
GROSS WEIGHT (KG)		44,5
QTY CARTON		1
QTY / MASTER CARTON		4
QTY PALLET/GROSS WEIGHT		BULK
QTY per 40' CT		191

To access to the digital version, scan this QR Code.



EZA FT CLIMATISEURS UK



Need some advice ?

Contact the Hotline on **+44 1376 428 006**



All our products come with a **2 Year Warranty**



More information on **www.eza.fr**